METRIC ALLTHREAD RECOMMENDED TIGHTENING TORQUE CLASS 4.6

METRIC ALLTHREAD - RECOMMENDED TIGHTENING TORQUE



<u>Note</u>:

The tightening torque values given in the table serve only as a guide. A k factor of 0.2 has been used which assumes threads are plain finish, burr free with a light oil coating.

It should be noted that these figures are based on the first tightening of single assemblies in isolation.

| Size | Pitch | Stress Area | Core Area | Tensile Strength | Proof Strength | Shear Strength | Recommer | ided Tighter | ning Torque |
|------|-------|-------------|-----------|---------------------|-------------------|-------------------|------------|--------------|-------------|
| | (mm) | (mm) | (mm) | (kN) | (kN) | (kN) | Plain (Nm) | Zinc (Nm) | HDG (Nm) |
| M3 | 0.50 | 5.0 | 4.5 | 2.0 | 1.1 | 1.1 | 0.4 | 0.3 | 0.9 |
| M4 | 0.70 | 8.8 | 7.8 | 3.5 | 2.0 | 1.9 | 1.0 | 0.7 | 2.2 |
| M5 | 0.80 | 14.2 | 12.7 | 5.7 | 3.2 | 3.0 | 2.1 | 1.5 | 4.4 |
| M6 | 1.00 | 20.1 | 17.9 | 8.0 | 4.5 | 4.3 | 3.5 | 2.5 | 7.4 |
| M8 | 1.25 | 36.6 | 32.8 | 14.6 | 8.2 | 7.9 | 8.6 | 6.0 | 18.0 |
| M10 | 1.50 | 58.0 | 52.3 | 23.2 | 13.1 | 12.6 | 17.0 | 11.9 | 35.6 |
| M12 | 1.75 | 84.3 | 76.2 | 33.7 | 19.0 | 18.3 | 29.6 | 20.7 | 62.1 |
| M14 | 2.00 | 115.0 | 104.7 | 46.0 | 25.9 | 25.1 | 47.1 | 33.0 | 98.9 |
| M16 | 2.00 | 157.0 | 144.0 | 62.8 | 35.3 | 34.6 | 73.5 | 51.4 | 154.3 |
| M18 | 2.50 | 192.0 | 175.0 | 76.8 | 43.2 | 42.0 | 101.1 | 70.8 | 212.3 |
| M20 | 2.50 | 245.0 | 225.0 | 98.0 | 55.1 | 54.0 | 143.3 | 100.3 | 301.0 |
| M22 | 2.50 | 303.0 | 281.0 | 121.2 | 68.2 | 67.4 | 195.0 | 136.5 | 409.5 |
| M24 | 3.00 | 353.0 | 324.0 | 141.2 | 79.4 | 77.8 | 247.8 | 173.5 | 520.4 |
| M27 | 3.00 | 459.0 | 427.0 | 183.6 | 103.3 | 102.5 | 362.5 | 253.7 | 761.2 |
| M30 | 3.50 | 561.0 | 519.0 | 224.4 | 126.2 | 124.6 | 492.3 | 344.6 | 1033.8 |
| M33 | 3.50 | 694.0 | 647.0 | 277.6 | 156.2 | 155.3 | 669.9 | 468.9 | 1406.8 |
| M36 | 4.00 | 817.0 | 759.0 | 326.8 | 183.8 | 182.2 | 860.3 | 602.2 | 1806.6 |
| M39 | 4.00 | 976.0 | 912.0 | 390.4 | 219.6 | 218.9 | 1113.4 | 779.4 | 2338.1 |
| M42 | 4.50 | 1120.0 | 1050.0 | 448.0 | 252.0 | 252.0 | 1375.9 | 963.1 | 2889.4 |
| M48 | 5.00 | 1470.0 | 1380.0 | 588.0 | 330.8 | 331.2 | 2063.9 | 1444.7 | 4334.1 |
| M56 | 5.50 | 2030.0 | 1910.0 | 812.0 | 456.8 | 458.4 | 3325.1 | 2327.6 | 6982.8 |
| M64 | 6.00 | 2680.0 | 2520.0 | 1072.0 | 603.0 | 604.8 | 5017.0 | 3511.9 | 10535.6 |
| | | | | | | | | | |

| Southeast Fastener | ABN 30117890114 | | |
|--------------------|--|--------------------|-------------------|
| Larapinta Branch: | 71 Axis Place, LARAPINTA QLD 4110 | TEL: 07 3273 4400 | FAX: 07 3272 4999 |
| Eagle Farm Branch: | 109A Links Avenue South, EAGLE FARM QLD 4009 | TEL: 07 3268 77 88 | FAX: 07 3268 5689 |

ALTHREAD MINIMUM TENSILE STRENGTH (MPA OR N/MM²)

| ALLTHR (MPa or N | | MINIMUM TEI | NSILE STR | RESS | | | | |
|---------------------|-------|-------------|-----------|-------|-------|-------------|---------|-------|
| Nominal | Pitch | Stress Area | Class | Class | Class | Sampsonrod™ | Hobrod™ | Brass |
| Size | mm | mm² | 4.6 | 8.8 | 10.9 | | | |
| M3 | 0.50 | 5.03 | 400 | 800 | 1040 | - | - | 400 |
| M4 | 0.70 | 8.78 | 400 | 800 | 1040 | - | - | 400 |
| M5 | 0.80 | 14.20 | 400 | 800 | 1040 | - | - | 400 |
| M6 | 1.00 | 20.10 | 400 | 800 | 1040 | 800 | 1040 | 400 |
| M8 | 1.25 | 36.60 | 400 | 800 | 1040 | 800 | 1040 | 400 |
| M10 | 1.50 | 58.00 | 400 | 800 | 1040 | 800 | 1040 | 400 |
| M12 | 1.75 | 84.30 | 400 | 800 | 1040 | 800 | 1040 | 380 |
| M14 | 2.00 | 115.00 | 400 | 800 | 1040 | 800 | 1040 | - |
| M16 | 2.00 | 157.00 | 400 | 800 | 1040 | 800 | 1040 | 380 |
| M18 | 2.50 | 192.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M20 | 2.50 | 245.00 | 400 | 830 | 1040 | 830 | 1040 | 380 |
| M22 | 2.50 | 303.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M24 | 3.00 | 353.00 | 400 | 830 | 1040 | 830 | 1040 | 380 |
| M27 | 3.00 | 459.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M30 | 3.50 | 561.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M33 | 3.50 | 694.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M36 | 4.00 | 817.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M39 | 4.00 | 976.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M42 | 4.50 | 1121.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M48 | 5.00 | 1473.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M52 | 5.00 | 1758.00 | 400 | 830 | 1040 | 830 | 1040 | - |
| M64 | 6.00 | 2676.00 | 400 | 830 | 1040 | 830 | 1040 | - |

OUTHEAST Fasteners

| Southeast Fastener | ABN 30117890114 | |
|--------------------|--|--|
| Larapinta Branch: | 71 Axis Place, LARAPINTA QLD 4110 | TEL: 07 3273 4400 FAX: 07 3272 4999 |
| Eagle Farm Branch: | 109A Links Avenue South, EAGLE FARM QLD 4009 | TEL: 07 3268 77 88 FAX: 07 3268 5689 |

ALTHREAD MINIMUM STRESS UNDER PROOF LOAD (MPA OR N/MM2)

| ALLTHR (MPa or N | | MINIMUM ST | RESS UND | DER PROOF | LOAD | | | |
|---------------------|-------|-------------|----------|-----------|-------|-------------|---------|-------|
| Nominal | Pitch | Stress Area | Class | Class | Class | Sampsonrod™ | Hobrod™ | Brass |
| Size | mm | mm² | 4.6 | 8.8 | 10.9 | | | |
| M3 | 0.50 | 5.03 | 225 | 580 | 830 | - | - | 160 |
| M4 | 0.70 | 8.78 | 225 | 580 | 830 | - | - | 160 |
| M5 | 0.80 | 14.20 | 225 | 580 | 830 | - | - | 160 |
| M6 | 1.00 | 20.10 | 225 | 580 | 830 | 580 | 830 | 160 |
| M8 | 1.25 | 36.60 | 225 | 580 | 830 | 580 | 830 | 160 |
| M10 | 1.50 | 58.00 | 225 | 580 | 830 | 580 | 830 | 160 |
| M12 | 1.75 | 84.30 | 225 | 580 | 830 | 580 | 830 | 160 |
| M14 | 2.00 | 115.00 | 225 | 580 | 830 | 580 | 830 | - |
| M16 | 2.00 | 157.00 | 225 | 580 | 830 | 580 | 830 | 160 |
| M18 | 2.50 | 192.00 | 225 | 600 | 830 | 600 | 830 | - |
| M20 | 2.50 | 245.00 | 225 | 600 | 830 | 600 | 830 | 160 |
| M22 | 2.50 | 303.00 | 225 | 600 | 830 | 600 | 830 | - |
| M24 | 3.00 | 353.00 | 225 | 600 | 830 | 600 | 830 | 160 |
| M27 | 3.00 | 459.00 | 225 | 600 | 830 | 600 | 830 | - |
| M30 | 3.50 | 561.00 | 225 | 600 | 830 | 600 | 830 | - |
| M33 | 3.50 | 694.00 | 225 | 600 | 830 | 600 | 830 | - |
| M36 | 4.00 | 817.00 | 225 | 600 | 830 | 600 | 830 | - |
| M39 | 4.00 | 976.00 | 225 | 600 | 830 | 600 | 830 | - |
| M42 | 4.50 | 1121.00 | 225 | 600 | 830 | 600 | 830 | - |
| M48 | 5.00 | 1473.00 | 225 | 600 | 830 | 600 | 830 | - |
| M52 | 5.00 | 1758.00 | 225 | 600 | 830 | 600 | 830 | - |
| M64 | 6.00 | 2676.00 | 225 | 600 | 830 | 600 | 830 | - |

OUTHEAST Fasteners

| Southeast Fastener | ABN 30117890114 | |
|--------------------|--|--|
| Larapinta Branch: | 71 Axis Place, LARAPINTA QLD 4110 | TEL: 07 3273 4400 FAX: 07 3272 4999 |
| Eagle Farm Branch: | 109A Links Avenue South, EAGLE FARM QLD 4009 | TEL: 07 3268 77 88 FAX: 07 3268 5689 |

ALLTHREAD MINIMUM PROOF LOAD (KN)

| 0 | U | 1 | | -[] | Ξ | A | S | Т |
|---|---|---|---|-----|---|---|---|---|
| F | А | s | т | Е | N | Е | R | S |
| - | | | | | | | | |

| ALLTHR | EAD - N | | |) (KN) | | | | |
|---------|---------|-------------|--------|---------|---------|-------------|---------|-------|
| Nominal | Pitch | Stress Area | Class | Class | Class | Sampsonrod™ | Hobrod™ | Brass |
| Size | mm | mm² | 4.6 | 8.8 | 10.9 | | | |
| M3 | 0.50 | 5.03 | 1.13 | 2.92 | 4.17 | - | - | 0.80 |
| M4 | 0.70 | 8.78 | 1.98 | 5.09 | 7.29 | - | - | 1.40 |
| M5 | 0.80 | 14.20 | 3.20 | 8.24 | 11.79 | - | - | 2.27 |
| M6 | 1.00 | 20.10 | 4.52 | 11.66 | 16.68 | 11.66 | 16.68 | 3.22 |
| M8 | 1.25 | 36.60 | 8.24 | 21.23 | 30.38 | 21.23 | 30.38 | 5.86 |
| M10 | 1.50 | 58.00 | 13.10 | 33.60 | 48.10 | 33.60 | 48.10 | 9.28 |
| M12 | 1.75 | 84.30 | 19.00 | 48.90 | 70.00 | 48.90 | 70.00 | 13.49 |
| M14 | 2.00 | 115.00 | 25.90 | 66.70 | 95.50 | 66.70 | 95.50 | - |
| M16 | 2.00 | 157.00 | 35.30 | 91.10 | 130.30 | 91.10 | 130.30 | 25.12 |
| M18 | 2.50 | 192.00 | 43.20 | 115.20 | 159.40 | 115.20 | 159.40 | - |
| M20 | 2.50 | 245.00 | 55.10 | 147.00 | 203.30 | 147.00 | 203.30 | 39.20 |
| M22 | 2.50 | 303.00 | 68.20 | 181.80 | 251.50 | 181.80 | 251.50 | - |
| M24 | 3.00 | 353.00 | 79.40 | 211.80 | 293.00 | 211.80 | 293.00 | 56.48 |
| M27 | 3.00 | 459.00 | 103.30 | 275.40 | 381.00 | 275.40 | 381.00 | - |
| M30 | 3.50 | 561.00 | 126.20 | 336.60 | 465.60 | 336.60 | 465.60 | - |
| M33 | 3.50 | 694.00 | 156.20 | 416.40 | 576.00 | 416.40 | 576.00 | - |
| M36 | 4.00 | 817.00 | 183.80 | 490.20 | 678.10 | 490.20 | 678.10 | - |
| M39 | 4.00 | 976.00 | 219.60 | 585.60 | 810.10 | 585.60 | 810.10 | - |
| M42 | 4.50 | 1121.00 | 252.20 | 672.60 | 930.40 | 672.60 | 930.40 | - |
| M48 | 5.00 | 1473.00 | 331.40 | 883.80 | 1222.60 | 883.80 | 1222.60 | - |
| M52 | 5.00 | 1758.00 | 395.60 | 1054.80 | 1459.10 | 1054.80 | 1459.10 | - |
| M64 | 6.00 | 2676.00 | 602.10 | 1605.60 | 2221.10 | 1605.60 | 2221.10 | - |
| | | | | | | | | |

| Southeast Fastener | ABN 30117890114 | |
|--------------------|--|--|
| Larapinta Branch: | 71 Axis Place, LARAPINTA QLD 4110 | TEL: 07 3273 4400 FAX: 07 3272 4999 |
| Eagle Farm Branch: | 109A Links Avenue South, EAGLE FARM QLD 4009 | TEL: 07 3268 77 88 FAX: 07 3268 5689 |

ALTHREAD MINIMUM ULTIMATE TENSILE LOAD (KN)



| ALLTHR | EAD - N | | IMATE TE | NSILE LOA | AD (KN) | | | |
|---------|---------|-------------|----------|-----------|---------|-------------|---------|--------|
| Nominal | Pitch | Stress Area | Class | Class | Class | Sampsonrod™ | Hobrod™ | Brass |
| Size | mm | mm² | 4.6 | 8.8 | 10.9 | | | |
| M3 | 0.5 | 5.03 | 2.01 | 4.02 | 5.23 | - | - | 2.01 |
| M4 | 0.7 | 8.78 | 3.51 | 7.02 | 9.13 | - | - | 3.51 |
| M5 | 0.8 | 14.20 | 5.68 | 11.36 | 14.77 | - | - | 5.68 |
| M6 | 1 | 20.10 | 8.04 | 16.08 | 20.90 | 16.08 | 20.90 | 8.04 |
| M8 | 1.25 | 36.60 | 14.60 | 29.28 | 38.06 | 29.28 | 38.06 | 14.64 |
| M10 | 1.5 | 58.00 | 23.20 | 46.40 | 60.30 | 46.40 | 60.30 | 23.20 |
| M12 | 1.75 | 84.30 | 33.70 | 67.40 | 87.70 | 67.40 | 87.70 | 32.03 |
| M14 | 2 | 115.00 | 46.00 | 92.00 | 119.60 | 92.00 | 119.60 | - |
| M16 | 2 | 157.00 | 62.80 | 125.60 | 163.30 | 125.60 | 163.30 | 59.66 |
| M18 | 2.5 | 192.00 | 76.80 | 159.40 | 199.70 | 159.40 | 199.70 | - |
| M20 | 2.5 | 245.00 | 98.00 | 203.30 | 254.80 | 203.30 | 254.80 | 93.10 |
| M22 | 2.5 | 303.00 | 121.20 | 251.50 | 315.10 | 251.50 | 315.10 | - |
| M24 | 3 | 353.00 | 141.20 | 293.00 | 367.10 | 293.00 | 367.10 | 134.14 |
| M27 | 3 | 459.00 | 183.60 | 381.00 | 477.40 | 381.00 | 477.40 | - |
| M30 | 3.5 | 561.00 | 224.40 | 465.60 | 583.40 | 465.60 | 583.40 | - |
| M33 | 3.5 | 694.00 | 277.60 | 576.00 | 721.80 | 576.00 | 721.80 | - |
| M36 | 4 | 817.00 | 326.80 | 678.10 | 849.70 | 678.10 | 849.70 | - |
| M39 | 4 | 976.00 | 390.40 | 810.10 | 1015.00 | 810.10 | 1015.00 | - |
| M42 | 4.5 | 1121.00 | 448.40 | 930.40 | 1165.80 | 930.40 | 1165.80 | - |
| M48 | 5 | 1473.00 | 589.20 | 1222.60 | 1531.90 | 1222.60 | 1531.90 | - |
| M52 | 5 | 1758.00 | 703.20 | 1459.10 | 1828.30 | 1459.10 | 1828.30 | - |
| M64 | 6 | 2676.00 | 1070.40 | 2221.10 | 2783.00 | 2221.10 | 2783.00 | - |

| Southeast Fastener | ABN 30117890114 | |
|--------------------|--|--|
| Larapinta Branch: | 71 Axis Place, LARAPINTA QLD 4110 | TEL: 07 3273 4400 FAX: 07 3272 4999 |
| Eagle Farm Branch: | 109A Links Avenue South, EAGLE FARM QLD 4009 | TEL: 07 3268 77 88 FAX: 07 3268 5689 |